



US010281234B1

(12) **United States Patent**
Burnsed, Jr.

(10) **Patent No.:** **US 10,281,234 B1**
(45) **Date of Patent:** ***May 7, 2019**

(54) **SLING ATTACHMENT DEVICE**

(56) **References Cited**

(71) Applicant: **Blue Force Gear, Inc.**, Pooler, GA (US)
(72) Inventor: **Ashley A. Burnsed, Jr.**, Port Wentworth, GA (US)
(73) Assignee: **BLUE FORCE GEAR, INC.**, Pooler, GA (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

U.S. PATENT DOCUMENTS

| | | | |
|----------------|---------|-------------------|-------------------------|
| 4,610,476 A * | 9/1986 | Keiner | A44B 11/06 294/149 |
| 4,982,522 A * | 1/1991 | Norton | F41C 33/00 224/220 |
| 5,246,154 A * | 9/1993 | Adams | A45F 3/14 224/150 |
| 8,516,732 B2 * | 8/2013 | Burnsed, Jr. | F41C 23/02 24/573.11 |
| 8,793,916 B2 * | 8/2014 | Rogers | F41C 23/02 24/2.5 |
| 9,528,795 B1 * | 12/2016 | Burnsed, Jr. | F41C 33/002 |

(Continued)

(21) Appl. No.: **15/700,974**

OTHER PUBLICATIONS

(22) Filed: **Sep. 11, 2017**

Blue Force Gear, Inc., Universal Wire Loop, <https://www.blueforcegear.com/universal-wire-loop-uw1-3-25.html>, accessed Nov. 2, 2015.

Related U.S. Application Data

Primary Examiner — Justin M Larson

(63) Continuation of application No. 15/387,952, filed on Dec. 22, 2016, now Pat. No. 9,791,237, which is a continuation of application No. 14/935,747, filed on Nov. 9, 2015, now Pat. No. 9,528,795.
(60) Provisional application No. 62/077,260, filed on Nov. 9, 2014.

(74) *Attorney, Agent, or Firm* — Bennet K. Langlotz; Langlotz Patent & Trademark Works, LLC

(51) **Int. Cl.**
F41C 33/00 (2006.01)
F41C 23/02 (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC **F41C 33/002** (2013.01); **F41C 23/02** (2013.01); **Y10S 224/913** (2013.01); **Y10T 24/12** (2015.01)

A sling attachment device has a body having a strap facility adapted for attachment of a sling strap, a flexible elongated tether having a first end attached to the body, the tether having a free end opposite the first end, and the body defining a receptacle operable to receive the free end of the tether, such that the tether may be threaded through an aperture on a rifle and received by the receptacle to secure the strap to the rifle. The tether may have a selected first width along at least a portion of its length, and the free end may have a second width greater than the first width. A ball may be attached to the free end. The body may define a channel having a width larger than the first width and smaller than the second width. There may be an aperture adjacent to the channel.

(58) **Field of Classification Search**
CPC ... **Y10T 24/3913**; **Y10T 24/141**; **Y10T 24/12**; **F41C 23/02**; **F41C 33/002**; **Y10S 224/913**
USPC **224/150**; **42/85**
See application file for complete search history.

20 Claims, 10 Drawing Sheets

