



US007959046B2

(12) **United States Patent**
Burnsed, Jr. et al.

(10) **Patent No.:** **US 7,959,046 B2**
(45) **Date of Patent:** **Jun. 14, 2011**

(54) **METHODS, SYSTEMS, AND APPARATUS FOR PROVIDING A MULTIPLE POSITION SLING FOR A FIREARM**

(75) Inventors: **Ashley A. Burnsed, Jr.**, Port Wentworth, GA (US); **Marvin C. Daniel**, Savannah, GA (US)

(73) Assignee: **Blue Force Gear, Inc.**, Pt. Wentworth, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1450 days.

(21) Appl. No.: **11/153,717**

(22) Filed: **Jun. 14, 2005**

(65) **Prior Publication Data**

US 2006/0011677 A1 Jan. 19, 2006

Related U.S. Application Data

(60) Provisional application No. 60/579,858, filed on Jun. 14, 2004.

(51) **Int. Cl.**
F41C 23/02 (2006.01)

(52) **U.S. Cl.** **224/150**; 224/578; 224/913

(58) **Field of Classification Search** 224/150, 224/149, 257, 258, 264, 578, 579, 913, 600, 224/250; 24/2.5, 302; 42/85, 94
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,812,123	A	11/1957	Girton	
4,511,070	A	4/1985	Hightower	
5,082,155	A *	1/1992	Salvador	224/150
5,246,154	A *	9/1993	Adams et al.	224/257
5,282,558	A *	2/1994	Martinez	224/150

5,810,219	A *	9/1998	Rosenfield	224/150
6,068,167	A *	5/2000	Hopson	224/150
6,520,390	B2 *	2/2003	Verdugo et al.	224/150
6,932,254	B2 *	8/2005	Eliason	224/150
7,059,502	B2	6/2006	Johnson	
7,069,624	B2	7/2006	Johnson	
2002/0020724	A1 *	2/2002	Lindsey	224/150
2004/0188476	A1	9/2004	Johnson	
2008/0217371	A1	9/2008	Wemmer	

OTHER PUBLICATIONS

The 2P: A Combat Tactical Sling System for the 21st Century <<http://redi-mag.com/2psling.php>>.

* cited by examiner

Primary Examiner — Nathan J Newhouse

Assistant Examiner — Corey N Skurdal

(74) *Attorney, Agent, or Firm* — Sutherland Asbill & Brennan LLP

(57) **ABSTRACT**

Methods, systems, and apparatus for supporting a firearm from a user. An apparatus according to one embodiment of the invention includes a sling capable of supporting a firearm from a portion of a user's body. The sling can include a strap capable of being supported by a portion of a user's body. The sling can also include a first connector mounted to a first portion of the strap, the first connector capable of mounting to a firearm connector. Furthermore, the sling can include a second connector mounted to a second portion of the strap, the second connector capable of mounting to a third connector, and further capable of mounting to a second firearm connector. Moreover, the sling can include a third connector mounted to a third portion of the strap, the third connector capable of mounting to the second connector, whereby the mounting of the second connector to the third connector creates a loop in the strap. In one aspect of the invention, the sling can include a fourth connector mounted to a fourth portion of the strap, wherein the fourth connector is capable of mounting to the second firearm connector.

26 Claims, 10 Drawing Sheets

