



(12) **United States Patent**
Burnsed, Jr.

(10) **Patent No.:** **US 8,516,732 B2**
(45) **Date of Patent:** **Aug. 27, 2013**

(54) **DETACHABLE SWIVEL AND ASSOCIATED MOUNT**

(75) Inventor: **Ashley A. Burnsed, Jr.**, Port Wentworth, GA (US)

(73) Assignee: **Blue Force Gear, Inc.**, Savannah, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/325,828**

(22) Filed: **Dec. 14, 2011**

(65) **Prior Publication Data**
US 2012/0174458 A1 Jul. 12, 2012

Related U.S. Application Data
(60) Provisional application No. 61/422,875, filed on Dec. 14, 2010.

(51) **Int. Cl.**
F41C 23/02 (2006.01)
A44B 18/00 (2006.01)
F16B 17/00 (2006.01)

(52) **U.S. Cl.**
USPC **42/85**; 24/573.11; 403/322.2; 411/348

(58) **Field of Classification Search**
USPC 42/85; 24/573.11, 648; 403/322.2; 411/348
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS			
2,480,662	A *	8/1949	McKinzie 42/85
2,642,689	A *	6/1953	Cline 42/85
4,571,872	A	2/1986	Johnson

5,067,267	A	11/1991	Ives	
5,394,594	A *	3/1995	Duran	24/453
5,692,654	A *	12/1997	Bell	224/150
6,152,645	A *	11/2000	Sanford	403/328
6,354,034	B1	3/2002	Norris, Sr.	
6,511,100	B1 *	1/2003	Le Clinche	285/316
7,654,027	B1	2/2010	Grover	
7,654,028	B1	2/2010	Grover	
7,814,697	B2	10/2010	Esch	
2006/0254113	A1 *	11/2006	Esch	42/85

FOREIGN PATENT DOCUMENTS

KR 2019940025966 12/1994

OTHER PUBLICATIONS

Search Report and Written Opinion for International Application No. PCY/US2011/064939 mailed Aug. 28, 2012.

* cited by examiner

Primary Examiner — Bret Hayes

(74) *Attorney, Agent, or Firm* — Sutherland Asbill & Brennan LLP

(57) **ABSTRACT**

Embodiments of the invention relate to a detachable swivel and associated mount. In one embodiment, a detachable swivel can be provided. The detachable swivel can include a housing with an axial cavity; at least one retention device; and an internal body operable to mount within the axial cavity, the internal body operable to contact the at least one retention device, wherein the internal body axially translates within the axial cavity between a first position and a second position; wherein an axial force applied to a portion of the internal body and away from the housing causes the internal body to translate between the first and second position.

19 Claims, 12 Drawing Sheets

