



US009791237B1

(12) **United States Patent**
Burnsed, Jr.

(10) **Patent No.:** **US 9,791,237 B1**
(45) **Date of Patent:** **Oct. 17, 2017**

- (54) **SLING ATTACHMENT DEVICE** 4,982,522 A * 1/1991 Norton F41C 33/00 224/220
- (71) Applicant: **Blue Force Gear, Inc.**, Pooler, GA (US) 5,246,154 A * 9/1993 Adams A45F 3/14 224/150
- (72) Inventor: **Ashley A. Burnsed, Jr.**, Port Wentworth, GA (US) 8,516,732 B2 * 8/2013 Burnsed, Jr. F41C 23/02 24/573.11
- (73) Assignee: **BLUE FORCE GEAR, INC.**, Pooler, GA (US) 8,793,916 B2 * 8/2014 Rogers F41C 23/02 24/2.5
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. 9,528,795 B1 * 12/2016 Burnsed, Jr. F41C 23/02

- (21) Appl. No.: **15/387,952**
- (22) Filed: **Dec. 22, 2016**

Related U.S. Application Data

- (63) Continuation of application No. 14/935,747, filed on Nov. 9, 2015, now Pat. No. 9,528,795.
- (60) Provisional application No. 62/077,260, filed on Nov. 9, 2014.

- (51) **Int. Cl.**
F41C 33/00 (2006.01)
F41C 23/02 (2006.01)
- (52) **U.S. Cl.**
CPC *F41C 23/02* (2013.01); *F41C 33/002* (2013.01); *Y10S 224/913* (2013.01); *Y10T 24/12* (2015.01)

- (58) **Field of Classification Search**
CPC ... Y10T 24/3913; Y10T 24/141; Y10T 24/12; F41C 23/02; F41C 33/002; Y10S 224/913
USPC 224/150; 42/85
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
4,610,476 A * 9/1986 Keiner A44B 11/06 294/149

- 2013/0333168 A1 12/2013 Burnsed, Jr.
- 2015/0128469 A1* 5/2015 Mossie F41C 23/02 42/90

OTHER PUBLICATIONS

Blue Force Gear, Inc., Universal Wire Loop, <https://www.blueforcegear.com/universal-wire-loop-uw1-3-25.html>, accessed Nov. 2, 2015.

* cited by examiner

Primary Examiner — Justin Larson
(74) *Attorney, Agent, or Firm* — Bennet K. Langlotz; Langlotz Patent & Trademark Works, Inc.

(57) **ABSTRACT**

A sling attachment device has a body having a strap facility adapted for attachment of a sling strap, a flexible elongated tether having a first end attached to the body, the tether having a free end opposite the first end, and the body defining a receptacle operable to receive the free end of the tether, such that the tether may be threaded through an aperture on a rifle and received by the receptacle to secure the strap to the rifle. The tether may have a selected first width along at least a portion of its length, and the free end may have a second width greater than the first width. A ball may be attached to the free end. The body may define a channel having a width larger than the first width and smaller than the second width. There may be an aperture adjacent to the channel.

36 Claims, 10 Drawing Sheets

